

AE-DC8322-G2PRO

4K/2160p + 1080p 2-Ch Dashboard Camera



- 4K/2160p Front Camera + 1080p Rear Camera
- FOVs: 135° Diagonal Front Camera/125° Diagonal Rear Camera
- f/1.75 Offers Perfect Night Image
- 3" 854 x 480 IPS (In-Plane Switching) Touchscreen
- Built-in Mic and Speaker for Audio In/Out
- Built-in Wi-Fi Module and Wi-Fi AP Function
- Built-in G-Sensor Records upon Car Crash or Strong Vibration (with Overwrite Protection)
- GPS Module with Speed Display and Route Tracking Playback
- Video Recording Card, MicroSD: Up to 256 GB
- Phone App: Live View, Record Playback, and Parameter Configuration
- Voice Commands: Snapshot, (Audio) Recording On, (Audio) Recording Off
- ADAS: "Traffic Light Turns Green," "Speed Limit Recognition"
- Easy Installation
- User Friendly, Plug and Play (Automatic Recording after Power on)
- Low Power Consumption, High Performance

The Hikvision AE-DC8322-G2PRO is a high resolution 2-channel dashcam that features easy installation and operation. The device communicates with its phone app through built-in Wi-Fi.

The built-in G-Sensor automatically locks the currently recording video when it senses a crash or strong vibration, to prevent it from being overwritten. MicroSD cards up to 256 GB are supported.

The built-in mic and speaker records and plays back audio.

Fields of View (FOV) are 135° Diagonal Front Camera/125° Diagonal Rear Camera, adjustable up and down.

The dashcam supports voice commands: "Snapshot," "(Audio) Recording On," and "(Audio) Recording Off."

Available model:

AE-DC8322-G2PRO







Œ


Specifications


	AE-DC8322-G2PRO
Came	
Image Sens	or CMOS
Resoluti	on 2160p @ 30 fps + 1080p @ 25 fps, 1080p @ 60 fps + 1080p @ 25 fps
Maximum Front Came	ra 135° (D), 124° (H)
Lens Angle Rear Came	
Apertu	
Video Compressi	
Displ	
	D Display time, date, etc.
Image Form	
Stora	eMMC Card: 64 GB built-in
	Microsp card: op to 250 ob (not included)
Communication Modu	
Sens	
Interfac	
Power Supp	
Audio Inp	
Audio Outp	
Gene	
Working Temperatu	re -20° to 65° C (-4° to 158° F)
Working Humid	ty 0% to 95%
Power Supp	ly 5 VDC, 2 A
Power Consumpti	on Maximum 6 W
Dimension (H x W x	L) 35.6 mm × 76.88 mm × 100 mm (1.40" × 3.03" × 4.00")
Weight (Approximat	e) 150 g (0.33 lb)

Dimensions











Accessories

