

EP-IPB120A-5-DL

EasyP



Features

- Easy-P with Artificial Intelligence
- Bullet IP camera
- 1/2.7" Progressive Scan CMOS
- 5 Megapixel (2960x1666)
- 2.8mm fixed lens
- Minimum illumination 0.01 Lux | 0 Lux with supplemental lighting
- IR range of 40 m
- Range White light 30 m
- DWDR
- Reset button
- Integrated microphone - Full compatibility with Uniview and Hikvision
- Supports UMD and Motion Detect 2.0: advanced motion detection that is triggered only by human and/or vehicle movement
- AI: intrusion detection, motion detection based on human detection. Reduces false alarms
- ONVIF Compatible
- P2P
- Weatherproof IP67
- PoE

Specifications

Brand	EASY-P
Image sensor	1/2.7" Progressive Scan CMOS
Maximum resolution	5 Megapixel (2960x1666)
Minimum illumination	Colour: 0.01 Lux @(F1.6, AGC ON)
Lighting Scope	GO to 40 m White light up to 30 m
Day/Night	Removable mechanical ICR filter
Electronic Shutter	1/3~1/100000 s
Main Stream rate	2880x1620@30fps; 2560x1440@30fps; 1920x1080@30fps; 1280*720@30fps
Extra Stream rate	1280x720@30fps, 720x480@30fps
Compression	H.264 / H.264+ / H.265 / H.265+ / JPEG / AVI / MJPEG
Lens	2.8 mm
Viewing Angle (FOV)	H: 109°, V: 58°, D: 129°
Image improvements	DWDR, BLC, 3D-DNR, AWB, ROI, Mirror Function, Privacy Mask, ROI
Motion detection and UMMD	Supports both functions
Smart Features	Native support of Motion Detect 2.0 and UMD
Audio	Integrated microphone
Audio Compression	G711A / U, AAC
Network interface	Ethernet 10 / 100M BaseT
Remote access	Web Browser, APP
Interoperability	ONVIF, plug&play with Uniview and Hikvision
P2P	Yes
Power	DC 12 V / 9 W max. / IEEE802.3af PoE
Degree of protection	Weatherproof IP67
Material	Metallic

Temp. operation -20° C ~ +60° C

Dimensions 70 x 67.5 x 169 mm

Weight 600 g
