

OC-UFO-F4N1-G

Hidden Camera PRO Range

Output 4in1

1/2.7" Aptina© 2.1 Mpx

3.7 mm Pinhole Lens

Minimum illumination 0.01 Lux

OSD Menu



HDTVI, HDCVI, AHD and Analog Hidden Camera

PRO Range

Flush mountable UFO type

1/2.7" Aptina© 2.1 Mpx

1080p (1920x1080)

Output 4in1

3.7 mm Pinhole Lens

0.01 Lux

2D DNR

IR Cut

DWDR

Specifications

Range	PRO
Image sensor	1/2.7" Aptina® 2.1 Megapixel (AR0237)
DSP	V30
Maximum resolution	1080p (1920x1080) to 25 fps
Resolution	TVI: 1080p (1920x1080) to 25 fps CVI: 1080p (1920x1080) to 25 fps AHD: 1080p (1920x1080) to 25 fps CVBS: 1000TVL
Lens	3.7 mm Pinhole
Minimum illumination	0.01 Lux
Video output	1 x BNC switchable between HDTVI / HDCVI / AHD / CVBS
Video output switching	Via Switch
Basic functions	OSD Menu (remote), Day/Night with IR CUT (ICR)
Configurable OSD functions	DWDR, 2D DNR, AE, AWB, AGC
Power	DC 12 V / 300 mA
Degree of protection	Interior
Dimensions	56 (D) x 86 (Ø) mm
Colour	Grey
Weight	200 g