

# SF-IPB025HA-2E

2 MP IP Camera  
1/2.8" Progressive Scan CMOS  
Compression H.265+, H.265, H.264+,  
H.264  
Built-in microphone  
Lens 2.8 mm / IR LEDs Range 30 m  
WEB, CMS Software, Smartphone  
and NVR



Safire  
IP camera  
ECO Range  
1/2.8" Progressive Scan CMOS  
2 Megapixel (1920x1080)  
2.8 mm Lens  
0 Lux  
IR Range 30 m  
Compression H.265+/H.265/H.264+/H.264  
Built-in microphone  
RJ-45 10/100 BaseT  
PoE IEEE802.3af  
Weatherproof IP66  
IR Cut  
WEB, CMS, Smartphone and NVR interface  
ONVIF Compatible

# Specifications

Brand	SAFIRE
Image sensor	1/2.8" Progressive Scan CMOS
Maximum resolution	2 Megapixel (1920x1080)
Main Stream rate	30 fps (1920 x 1080, 1280 x 960, 1280x720)
Extra Stream rate	30 fps x (640 360,x 320 240)
Compression	H.265+, H.265, H.264+, H.264
Bitrate	32 Kbps – 8 Mbps
Lens	2.8 mm (H: 114°, V: 62°, D: 135°)
Minimum illumination	0.028 Lux (colour) / 0 Lux (B/N)
Infrared lighting	0 Lux / IR LEDs (30 m)
Image improvements	WDR, BLC, 3D-NR, AWB, ROI, Motion detection, Mirror
Day / Night	Removable mechanical ICR filter
Audio	Integrated microphone
Network interface	Ethernet 10/100 BaseT
Remote access	Web browser, Safire Control Center Smartphone App and PC Software
Interoperability	ONVIF, PSIA, CGI, ISAPI
Power	12 VDC / 300 mA, PoE IEEE802.3af
Degree of protection	Weatherproof IP66
Temp. operation	-30° C ~ +60° C
Dimensions	177.6 (D) x 67.8 (W) x 66.2 (H) mm
Base dimensions	55 mm (Ø) x 3 bolts
Weight	270 g