

SF-VIK002-S-IP-E

ECO Video Intercom Entry Kit

Tecnología IP & WiFi

Includes Echo Board and Monitor

MF Reader | PoE Standard

Mobile App with P2P from the board

Surface mounting



Safire

Intercom Kit

IP Interface

Kit consisting of: SF-VI111-IPW-1MF outdoor video intercom entry panel with 2Mpx HD camera, SF-VIDISP01-7IP-E ECO indoor monitor with 7" TFT LCD screen and power supply

Monitoring via Safire Control Center Software or mobile App by connecting panel via P2P

Specifications

Panel	
Brand	Safire
Model	SF-VI111-IPW-1MF
Operating system	LINUX OS
Image sensor	1/3" 2 Megapixel CMOS
Audio	Bidirectional audio with microphone and speaker
Access Control	Door opening with MF card 13.65MHz to 256
Keypad	Mechanical button with LED backlit name-tag
Relay	1 for lock control.
Inputs	Exit button, feedback, door sensor, tamper
Remote access	Web browser, phone app or Safire Control Center-software
Network interface	Ethernet 10/100 BaseT, WiFi
Power	DC 12 V / 1000 mA max. / IEEE802.3af PoE
Remote access	Mobile app or Safire Control Center-software
Degree of protection	IP65
Material	Plastic
Temp. operation	-40° C ~ +53° C
Dimensions	138 (H) x 65 (W) x 27 (D) mm
Weight	400 g
Monitor	
Brand	Safire
Model	SF-VIDISP01-7IP-E
LCD	7" 1024x600, Capacitive
Operation mode	Tactile Buttons
Inputs	8 Configurable alarm entries
Audio	Two-way audio with microphone and speaker with noise reduction
Memory	Slot MicroSD up to 32GB
Network interface	Ethernet 10/100 BaseT / RS485 / RTSP
Power	DC 12 V / 1000 mA max. / standard PoE (IEEE802.3af)
Temp. operation	-10° C ~ +55° C
Dimensions	200 (H) x 140 (W) x 23.6 (D) mm
Weight	355 g